

DIESEL EXHAUST FLUID TRANSFER EQUIPMENT

DC-30 Options

Pump Assembly Options:

- Flooded suction pump
- Self-priming, seal-less, mag drive pump
- Gas powered engine
- 230V AC electric motor

Meter Assembly Options:

- Turbine meter
- Electronic register
- Electronic printer
- Pre-set
- Poly spit tank plumbed to air eliminator
- Non Weights and Measures approved meter

Hose Assembly Options:

- Longer suction and discharge lengths
- Drumming nozzle, closed-loop, dry-break, and quick disconnect fitting packages

Filtration Assembly Options:

- Stainless steel cartridge or bag housing
- Polypropylene cartridge housing

Semler Industries Inc.

3800 North Carnation Street
Franklin Park, IL 60131 USA
Phone: (847) 671-5650
Fax: (847) 671-7686
semler@semlerindustries.com

www.semleindustries.com

DEF-Distributor™ Cart **DC-30**

Operates at 30 GPM*

Ideal for transferring DEF when portability is desired & budget is limited



Approximate Footprint:
24" W x 24" L x 50" H

DC-30 INCLUDES

- 30 GPM* nominal flow rate
- Stainless steel self-priming pump
- 115V AC, single phase electric motor with manual motor starter
- 25' power cord with plug
- 15 Amp, plugs into standard wall outlet
- Positive displacement flow meter
- Mechanical register and printer
- Air Eliminator
- Stainless steel strainer**
- Weights and Measures approved for custody transfer
- Hose hanger
- 1" x 10' Suction hose with MNPT ends
- 1" x 20' Discharge hose with MNPT ends
- Heavy duty mobile DEF cart
- All fluid contact equipment meets ISO 22241-3 standard for material compatibility
- System is passivated, tested, flushed, sealed and crated for quality assurance
- Dual sided guards for pump and plumbing protection
- Stainless steel fitting tray
- Meter guard for added protection
- Twin backside rails for filter protection
- Hook straps to secure system inside of truck

*Flow rate based off open hose ends.

**Stainless steel strainer is not needed if a filter housing option is chosen.

Unit shown includes: Self-priming pump, positive displacement meter, mechanical register and printer, standard hose lengths, spit tank option, and quick connect fitting package.



Semler's Complete Line of DEF-Distributor™ Transfer Equipment



Model
DD-25
Operates at 25 GPM*




Model
DC-30
Operates at 30 GPM*



Model
DD-45
Operates at 45 GPM*



Model
DD-70
Operates at 70 GPM*



Model
DD-120
Operates at 120 GPM*



Model
DD-250
Operates at 250 GPM*

*Flow rate based off open hose ends.

Other Offerings through Semler



Fuel Polishing



Closed Loop Transfer Couplers



Polyethylene Bulk Storage Tanks



Absorbent Media & Spill Kits



Lube Oil Transfer Carts



Mini-Bulk & Dispenser Systems



Heavy-Duty Hose Reels for Transfer & Dispensing



Bulk DEF Hose & Assemblies



High-Flow Transfer Pumps

Don't see an option that meets your needs? Just ask, the options and configurations available are endless...

Semler Industries brings over 100 years of meeting customers' demands and 50+ years serving the petroleum and chemical markets together to meet the demands of DEF manufacturers, distributors, and users for the petroleum retail market. From low-flow drum dispensing to high-volume storage and transfer, everything we do is focused on maintaining the quality of the fluid, and making it easy for you to handle.



Semler Industries Inc.

3800 North Carnation Street
Franklin Park, IL 60131 USA
Phone: (847) 671-5650

Fax: (847) 671-7686

semler@semlerindustries.com

www.semelerindustries.com